






Interoperability list for FaxGwise FoIP

Company	Product	Release	H.323 Protocol						SIP Protocol						Security TLS/SRTP	
			Fax		Supplementary Services				Fax		Supplementary Services					
			Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting	Call diversion/Call deflection	Call Transfer	Redirecting number		
	3CX Phone System	V9.0							■4	-	-	-	-	■4		
	Aastra 400	R1							■	-	■	-	■1	■		
	Aastra 400	R2							■	-	■	■	■1	■		
	Aastra 800	R9.1							■4	-	-	-	■1 4			
	Aastra 5000	R5.1							■	-	-	-	■1	-		
	BP250		■	-	■	-	■1	■								
	IntelliGate	7.9							■	■	-	-	■1	-		
	MD110		■	-	■	-	■1	■								
	MX-ONE	V4.1	■	-	■	-	■1	■	■	■	-	-	■1 4	■		
	OpenCom 1000	txl 5110							■	-	-	-	■1	■		
OpenCom X320	R9.10							■4	-	-	-	■4	■4			
	OmniPCX Office (OXO)	6	-	-	-	-	■	-	-	9.60 0	-	-	■0	-		
		7	-	-	-	-	■	■	■	9.60 0	-	-	■	■		
	OmniPCX Enterprise (OXE)	5	-	■0	-	-	■1	-	-	-						
		6	-	9.6 00	-	-	■1	-	-	-	-	-	-	-	-	
		7.1-f5.401-17-d	-	9.6 00	-	-	■1	-	-	-	-	-	-	-	-	
		8.0-g1.302-7	-	9.6 00	-	-	■1	-	-	-	9.60 0	■	■	■	■	
		R9.1-i1.605.33c	-	9.6 00	-	-	■1	■	-	-	9.60 0	■	■	■	■	
R10.0-j1.410-45	-	9.6 00	-	-	■1	■	-	-	9.60 0	■	■	■	■			
	Asterisk	1.8.3.3							■	■	-	■	■	-		
	Mediant 600	6.00AL.018.003							■	■	-	-	■1	-		
	Mediant 800	6.00AL.018.003							■	■	-	-	■1	-		
	Mediant 1000	6.00AL.018.003							■	■	-	-	■1	-		

Trademarks




All names of products or services used are trademarks or registered trademarks (also without specified indication) of the respective private or legal persons and are therefore subject to legal regulations.

Legend:

■ = Functional; - = Not yet supported; ○ = Unconfirmed; 1 = Simulated; 2 = QSIG; 3 = No TLS/SRTP Support; 4 = SIP-Client

No responsibility is taken for the correctness of this information.

This compilation exclusively contains devices tested by us - hence interoperability of XCAPi with devices not listed here is still possible.

Company	Product	Release	H.323 Protocol						SIP Protocol						Security TLS/SRTP
			Fax		Supplementary Services				Fax		Supplementary Services				
			Sofffax 14.400 bps	T.38 14.400 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	Sofffax 14.400 bps	T.38 14.400 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	
AVAYA	Communication Manager	3.0	■	9.600	■2	-	■2	■2							
		4.0	■	9.600	■2	-	■2	■2							
		5.0	■	9.600	■2	-	■2	■2	■	9.600	■	-	■	■	
		6.0	■	9.600	■2	-	■2	■2	■	9.600	■	-	■	■	
	IP Office	3x	■	-	-	-	■1	-							
		4.0	■	-	■2	-	■	-							
		5.0	■	-	■2	-	■	-	■	-	-	-	■1	-	
		6.0	■	-	■2	-	■	-	■	-	-	-	■	-	
		7.0	■	-	■2	-	■	-	■	-	-	-	■	-	
		8.0	■	-	■2	-	■	-	■	■	-	-	■	■	
	Integral Enterprise	IEE3							■	-	■	-	■1	■	
		IEE4							■	■0	■	-	■	■	
		IEE5							■	■	■	-	■	■	
		IEE6							■	■	■	-	■	■	
		IEE7							■	■	■	-	■	■	
	SES (SIP Enablement Services)	SES-5.2.1.0-016.4								■	■0 3	■	-	■	■
	Session Manager [please ask for device-dependent SIP-Trunk interoperability]	6.0								■	■3	-	-	■	■
	 FRITZ!Box Fon WLAN 7270	54/74.04.86								■4	■4	-	-	■4	-
	 beroNet	bero*fix	1.12rc10							■	■	-	-	-	-
	 brekeke	brekeke PBX	2.4.5.5							■	-	■	-	■	-
brekeke SIP Server		2.4.5.5							■	-	■	-	■	-	









Trademarks

All names of products or services used are trademarks or registered trademarks (also without specified indication) of the respective private or legal persons and are therefore subject to legal regulations.

Legend:

■ = Functional; - = Not yet supported; ○ = Unconfirmed; 1 = Simulated; 2 = QSIG; 3 = No TLS/SRTP Support; 4 = SIP-Client

No responsibility is taken for the correctness of this information. This compilation exclusively contains devices tested by us - hence interoperability of XCAPi with devices not listed here is still possible.

Company	Product	Release	H.323 Protocol						SIP Protocol						Security
			Fax		Supplementary Services				Fax		Supplementary Services				
			Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	
	CallManager Express		■	■	■	-	■	■	■	■	■	■	■	■	
	CallManager	3.3	■	-	■	-	■1	■							
		4.1	■	-	■	-	■1	■							
		4.2	■	■	■	-	■1	■							
		4.3	■	■	■	-	■1	■							
	Unified Communications Manager	5.x	■	■	■	-	■1	■	■	■	■	■	■	■	■
		6.x	■	■	■	-	■1	■	■	■	■	■	■	■	■
		7.x	■	■	■	-	■1	■	■	■3	■	■	■	■	■
8.x		■	■	■	-	■1	■	■	■3	■	■	■	■	■	
VoIP Gateways		■	■	■	-	■	■	■	■	■	■	■	■		
	Dialogic 1000 Media Gateway Series	V6.0	-	-	-	-	-	-	■	■	-	-	■1	-	
	IP400	5.01	■	9.600	■	■	■	■							
	IP800	8.00	■	9.600	■	■	■	■	■	■3	-	-	■1	■	■
	IP3000	6.00	■	9.600	■	■	■	■	■	■	-	-	■1	■0	-
	IP6000	8.00	■	9.600	■	■	■	■	■	■3	-	-	■1	■	■
	1722 VoIP	V7.60							-	■	-	■	■	-	
	1723 VoIP	V7.60							-	■	-	■	■	-	
	1724 VoIP	V7.60							-	■	-	■	■	-	
	1823 VoIP	V7.60							-	■	-	■	■	-	
	iPECS-LIK 50								■	-	-	-	■1	-	
	Mediatrix 4400 Series								■	■	-	■	■	-	
	Office Communications Server 2007	3.0.6362.0							■	-	-	-	■1	-	
	OCS 2007 Speech Server	2.0.61363.0							■0	-	-	-	■1	-	
	Lync Server 2010	4.0.7577.0							■	-	-	-	■1	-	■
	3300 Integrated Communications Platform	10.2.0.26							■	■	■	-	■	■	

Trademarks








All names of products or services used are trademarks or registered trademarks (also without specified indication) of the respective private or legal persons and are therefore subject to legal regulations.






Legend:

■ = Functional; - = Not yet supported; ○ = Unconfirmed; 1 = Simulated; 2 = QSIG; 3 = No TLS/SRTP Support; 4 = SIP-Client

No responsibility is taken for the correctness of this information.

This compilation exclusively contains devices tested by us - hence interoperability of XCAPi with devices not listed here is still possible.

Company	Product	Release	H.323 Protocol						SIP Protocol						Security TLS/SRTP	
			Fax		Supplementary Services				Fax		Supplementary Services					
			Softfax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	Softfax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number		
	BCM200		■○	-	-	-	■○	-								
	CS 1000 (SIP Gateway with MPLR22452)	5.0 (sse-5.50.12.)							■○	■	■	■	■	■○		
	CS 1000 (SIP Gateway with MPLR25946)	6.0							■	■	■	■	■	■		
	Inalp 2400	R3.2	■	9.600	-	■	■	-	■	-	-	-	■○	-		
	SmartNode 4630 Series	R3.2	■	9.600	-	■	■	-	■	-	-	-	■○	-		
	SmartNode 4630 Series	R4.2	■	■	-	■	■	■	■	■	-	■	■	■		
	SmartNode 4630 Series	R5.4	■	■	-	■	■	■	■	■	-	■	■	■		
	KX-NCP500 / KX-NCP1000	OneNet 4.2.003	-	■	-	-	■	-								
	KX-TDE100 / KX-TDE200 / KX-TDE600	OneNet 4.2.003	-	■	-	-	■	-								
	OfficeServ 7200	4.60							■	■	■○	-	■	■		
	OfficeServ 7400	4.60							■	■	■○	-	■	■		
	Vega 50 Europa BRI	R8.6							■	■○	-	-	-	-		
	Voice Switch / ShoreGear	11.1							■	-	■	-	■	■		
	Voice Switch / ShoreGear	12.1							■	-	■	-	■	■		
	HiPath 2000	V1	■	■○	■	-	■	■	■	-	-	-	■	-		
	HiPath 3000 / HG 1500 [please ask for device-dependent H.323-Trunk interoperability]	V7	■	■	■	-	■	■	■	■	-	-	■ 4	■		
	HiPath 3000 / HG 1500	V8							■	■	-	-	■ 4	■		
	HiPath 3000 / HG 1500	V9							■	■	-	-	■ 4	■		
	HiPath 4000 / HG 3500	V3	■	9.600	■	-	■	■								
	HiPath 4000 / HG 3500	V4	■	■	■	-	■	■	■	-	-	-	■	■		
	HiPath 4000 / HG 3500	V5	■	■	■	■	■	■	■	■	■	■	■	■		
	HiPath 4000 / HG 3500	V6	■	■	■	■	■	■	■	■	■	■	■	■		
	HiPath 8000	V3								■	■○	■	■	■	■	
	OpenScope Voice	V5								■	■	■	■	■	■	
	OpenScope Voice	V6								■	■	■	■	■	■	
	OpenScope Office LX	V3								■	■	-	-	■ 4	■	

Company	Product	Release	H.323 Protocol						SIP Protocol						Security
			Fax		Supplementary Services				Fax		Supplementary Services				
			Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer	Redirecting number	
 SIPfoundry <small>open source community.</small>	sipXecs <small>[please ask for device-dependent interoperability]</small>	4.40							■	■	■ 4	-	■ 1	-	
 SWYX	SwyxWare	5.0	■○	-	■	-	■1	-	■○	-	-	-	-	-	
	SwyxWare	6.20.0240							■	■○	-	-	■1	-	
 TELEBAU <small>Kommunikation in Bestform</small>	IP Gate 104/208		■	-	-	-	■1	-							
	IP Gate 312		■	-	-	-	■1	-							
 TELES <small>Communication Systems</small>	TELES.ISWITCH (SS7)		-	■	-	■	■1	■							
 tevitel <small>telecommunications</small>	tevitel.iPBX-VoIP-Modul	6.x	■	■	■○	■	■	■							

Trademarks















All names of products or services used are trademarks or registered trademarks (also without specified indication) of the respective private or legal persons and are therefore subject to legal regulations.
Legend:

■ = Functional; - = Not yet supported; ○ = Unconfirmed; 1 = Simulated; 2 = QSIG; 3 = No TLS/SRTP Support; 4 = SIP-Client

No responsibility is taken for the correctness of this information.

This compilation exclusively contains devices tested by us - hence interoperability of XCAPi with devices not listed here is still possible.

Interoperability list / SIP Provider

Company	Website	SIP Protocol							Security	
		Link		Fax		Supplementary Services				
		SIP-Trunk	SIP-Client	Sofffax 14.400 bps	T.38 14.4000 bps	Message waiting indication	Call diversion/Call deflection	Call Transfer		Redirecting number
	http://www.1und1.de		■	■○				■1		
	http://www.babytelusa.com		■	■	■			■1		
	http://www.babytel.ca		■	■	■			■1		
	http://www.dus.net		■	■○				■1		
	http://www.gafachi.com		■	■	■			■1		
	http://www.nfon.net		■	■	■			■1		
	http://www.portunity.net		■	■○				■1		
	http://www.purtel.com		■	■○				■1		
	http://www.myqsc.de	■	■		■			■1		
	http://www.sipgate.de		■	■○				■1		
	http://www.live.sipgate.de		■	■○				■1		
	http://www.live.sipgate.de/trunking/	■	■	■○				■1		
	http://www.speednetwork.de		■	■				■1		
	http://www.swissipcom.ch		■	■	■			■1		
 Online	http://www.t-online.de		■	■				■1		
	http://www.toplink.de		■	■○	■			■1		
	http://www.wobcom.de	■	■	■				■		
	http://www.xpirio.com		■	■○				■1		

Trademarks

All names of products or services used are trademarks or registered trademarks (also without specified indication) of the respective private or legal persons and are therefore subject to legal regulations.
Legend:

■ = Functional; - = Not yet supported; ○ = Unconfirmed; 1 = Simulated; 2 = QSIG; 3 = No TLS/SRTP Support; 4 = SIP-Client

No responsibility is taken for the correctness of this information.

This compilation exclusively contains devices tested by us - hence interoperability of XCAPi with devices not listed here is still possible.